

The company

The Size Surfaces, S.L.

P.I. Camí Fondo, Supoi 8.
C/dels Ibers, 31 12550
Almazora (Castellón)
Spain

Hereby declares that:

The product **Neolith® non-slip floor** manufactured at its plant can be offered in slip resistance categories Class 1, Class 2 or Class 3 pursuant to ENV 12633 standards with the following guarantees:

The product is guaranteed for 2 years once installed as long as the treated material was installed in accordance with these conditions:

- Install the flooring in a clean manner.
- Deep clean all remains from the construction work without scratching the surface and without using abrasive products. Use a cleaner for non-slip treated floors.
- Avoid soaking the treated floor with cement derivatives or cement adhesive, etc.
- Once the flooring is installed, maintain the characteristics by following the *“Cleaning Protocol for Neolith Non-Slip Floors.”* (Annex)

Almazora, July 2016



THE SIZE SURFACES, S.L.
B-85171023
P.I. CAMÍ FONDO, SUPOI 8, C/ DELS IBERS Nº 31
C.P. 12550 ALMAZORA (CASTELLÓN)

Fábrica y oficina central *Factory & main office*
P.I. Camí Fondo, Supoi 8, C/ dels Ibers, 31 ■ 12550 Almassora-Castellón (España) ■ +34 964 652 233 ■ info@thesize.es
Dirección postal *Postal address*
Apartado 485 - C.P. 12540 Vila Real-Castellón (España)
www.neolith.com

THE SIZE SURFACES, S.L., inscrita en el Registro Mercantil de Castellón. Tomo 1.580, libro 1.142, folio 225, hoja CS-31918 - CIF B85171023

ANNEX I

CLEANING PROTOCOL FOR NEOLITH NON-SLIP FLOORS

DAILY CLEANING

- Cleaning products: pH neutral products to avoid deteriorating the non-slip treatment.
- Cleaning method: Mechanical cleaning with sweeping, mopping and liquid residue absorption.

WEEKLY CLEANING

- Cleaning products: Use non-aggressive disinfectant (the direct use of bleach is not recommended). A product may be used that removes lime and mineral salt remains the water leaves on the flooring or ammonia-based detergents.
- Cleaning method: Mechanical brushing to remove lime or mineral remains incusted in the pores.

MONTHLY CLEANING

- Cleaning products: Slip resistance floor cleaners such as “*Cleaner for Non-Slip Treated Flooring*” by Johnson España División Antideslizantes S.L. which helps remove microbial and bacteriological remains and helps maintain non-slip areas.
- Cleaning method: Brush the areas with the product. Let the cleaning product soak in. Rinse and vacuum the remaining liquid.

Fábrica y oficina central *Factory & main office*
 P.I. Camí Fondo, Supoi 8, C/ dels Íbers, 31 ■ 12550 Almassora-Castellón (España) ■ +34 964 652 233 ■ info@thesize.es
 Dirección postal *Postal address*
 Apartado 485 - C.P. 12540 Vila Real-Castellón (España)
www.neolith.com

THESIZE SURFACES, S.L., Inscrita en el Registro Mercantil de Castellón. Tomo 1.580, libro 1.142, folio 225, hoja CS-31918 - CIF B85171023